



SPECIFICATION

DRAIN SOLVENT WELD WHITE ASTM D2729

DRAIN SOLVENT WELD PVC

Pacific Plastics ASTM D2729 PVC pipe is produced for Sewer/Drain and other non-pressure applications. The compound is PVC 1120 Type 1 Grade 1, with a cell class of 12454B per ASTM D1784.

Pacific Plastics produces its Sewer & Drain pipe in strict compliance to ASTM D2729. The solvent cement shall comply with ASTM D2564.

PVC Sewer/Drain pipe ASTM D2729 is produced in White color and in 10 foot lengths only and is available both in Solid and Perforated.

Perforated pipe specification:

- 2 rows of holes, 120° apart, parallel to the axis of the pipe
- Holes are 1/2" in diameter and are on 5" center

The outside diameter and wall thickness of PVC Sewer/Drain ASTM D2729 are measured in accordance to ASTM D2122 and are shown in the following table:

DIMENSIONS

Size (inch)	OD (Outside Diameter)	T (Wall Thickness)	C (Approx Bell Depth)
3	3.250	0.070	1.50
4	4.215	0.075	1.75
6	6.275	0.100	3.00

WEIGHTS

Size (inch)	LBS/100'
3	46.00
4	63.00
6	126.00

Size
 OD Inch Outside Diameter
 T Thickness
 C Approx. Bell Depth

